

Quick Mixing Reference

PRODUCT NAME	SERIES		MIXING	APPLICATION	ACTIVATOR	UNI-THINNER			
			RATIO	METHOD		FAST	MEDIUM	SLOW	VERY SLOW
PRIMERS: OPTIONAL									
1K ETCH PRIMER (AU)	632 Series	GREY / BLACK / WHITE	R.F.U.	SPRAY	None	None			
LICP 200 EPOXY PRIMER		GREY	10:1+25%	SPRAY	EKP200	171	172	173	174
LICP 201 EPOXY PRIMER		WHITE	10:1+25%	SPRAY	EKP200	171	172	173	174
TOPCOATS:									
LIC 30 ACRYLIC ENAMEL	GLOSS	VARIOUS COLOURS	R.F.U.	BRUSH OR ROLLER	None	R.F.U.			
			+25%	SPRAY	None	ACETONE	MULTI PURPOSE THINNERS		
LIC 40 POLYURETHANE ENAMEL	GLOSS	VARIOUS COLOURS	4:1	BRUSH OR ROLLER	LK40	R.F.U.			
			4:1+0-25%	SPRAY	LK40	171	172	173	174
			4:1+25%	ELECTRO-STATIC	LK40	174			
LIC 43 LOW GLOSS POLYURETHANE ENAMEL	LOW GLOSS	VARIOUS COLOURS	4:1	BRUSH OR ROLLER	LK40	R.F.U.			
			4:1+0-25%	SPRAY	LK40	171	172	173	174
			4:1+25%	ELECTRO STATIC	LK40	174			