



# Material Safety Data Sheet

## 1. PRODUCT AND COMPANY IDENTIFICATION

**Product name:** UNI-SOLVENT - SLOW  
**Product code:** 173  
**Print Date:** 11/Jan/2010  
**Revision Date:** 04/Jan/2010  
**Recommended use:** For coating metal containers and similar products.

### Company Identification:

The Valspar Corporation  
210 CROSBY  
PICAYUNE, MS 39466

**Manufacturer's Phone:** 1-601-798-4731

**24-Hour Medical Emergency Phone:** 1 (888) 345-5732

### Supplier:

De Beer Australia Pty Ltd  
Unit 11, 8 Kerta Road  
Kincumber, NSW, Australia  
Phone 02-43684054

**Australia Poisons Information Centre 24 hours:** 131-126

## 2. HAZARDS IDENTIFICATION

**Classified as hazardous according to criteria of NOHSC.**  
**Classified as DANGEROUS according to the Australian Dangerous Goods Code.**

### Indication of danger:

F - Highly flammable  
Xn - Harmful  
N - Dangerous for the environment  
Carc. cat. 3

### Risk Phrases

R11 - Highly flammable.  
R20 - Harmful by inhalation.  
R36 - Irritating to eyes.  
R40 - Limited evidence of a carcinogenic effect.  
R65 - Harmful: may cause lung damage if swallowed.  
R51/53 - Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

## 2. HAZARDS IDENTIFICATION

### S-phrase(s)

S 9 - Keep container in a well-ventilated place.  
S16 - Keep away from sources of ignition - No smoking.  
S33 - Take precautionary measures against static discharges.  
S60 - This material and its container must be disposed of as hazardous waste.  
S61 - Avoid release to the environment. Refer to special instructions/safety data sheets.  
S23 - Do not breathe gas/fumes/vapour/spray.  
S51 - Use only in well-ventilated areas.  
S62 - If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.  
S36/37 - Wear suitable protective clothing and gloves.

## 3. COMPOSITION / INFORMATION ON INGREDIENTS

Ingredient Name CAS-No.	Approx. Weight %	Chemical Name
SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM. 64742-95-6	10-30	Petroleum naphtha, light aromatic
SOLVENT NAPHTHA (PETROLEUM), HEAVY AROM. 64742-94-5	10-30	Solvent naphtha, petroleum, heavy arom.
n-BUTYL ACETATE 123-86-4	10-30	n-Butyl acetate
1,2,4-TRIMETHYLBENZENE 95-63-6	10-30	1,2,4-Trimethylbenzene
ACETONE 67-64-1	10-30	Acetone
2-BUTOXYETHYL ACETATE 112-07-2	5-10	Ethylene glycol, monobutyl ether acetate
XYLENE 1330-20-7	5-10	Xylenes (o-, m-, p- isomers)
NAPHTHALENE 91-20-3	1-5	Naphthalene
ETHYLBENZENE 100-41-4	1-5	Ethyl benzene
CUMENE 98-82-8	0.2-0.5	Cumene

If this section is blank, there are no hazardous components per NOHSC guidelines.

## 4. FIRST AID MEASURES

### General

If symptoms persist, call a physician. Never give anything by mouth to an unconscious person.

### Skin:

Take off all contaminated clothing immediately. Wash off immediately with soap and plenty of water. Do NOT use solvents or thinners.

### Eyes:

Remove contact lenses. In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Keep eye wide open while rinsing.

### Inhalation:

Move to fresh air. If victim is unconscious but breathing: Victim to lie down in the recovery position, cover and keep him warm. If not breathing, give artificial respiration. Obtain medical attention.

## 4. FIRST AID MEASURES

### Ingestion:

Keep at rest. If swallowed, seek medical advice immediately and show this container or label. Do NOT induce vomiting.

## 5. FIRE FIGHTING MEASURES

<b>Hazchem Code:</b>	3[Y]E
<b>Flash point:</b>	-3
<b>Lower explosive limit:</b>	1
<b>Upper explosive limit:</b>	13
<b>Autoignition temperature:</b>	not determined

### The following actions are recommended

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire will produce dense black smoke containing hazardous combustion products (see heading 10).  
Wear self contained breathing apparatus for fire fighting if necessary.  
Cool containers / tanks with water spray.

### Suitable extinguishing media

Suitable extinguishing media  
Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry powder  
Extinguishing media which must not be used for safety reasons  
High volume water jet

## 6. ACCIDENTAL RELEASE MEASURES

### Personal precautions:

Exclude non essential personnel. Remove all sources of ignition. Ensure adequate ventilation. Do not breathe vapours/dust.

### Environmental precautions:

Local authorities should be advised if significant spillages cannot be contained.

### Methods for cleaning up:

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Clean with detergents. Avoid solvents.

## 7. HANDLING AND STORAGE

### Handling:

Operators should wear anti-static footwear and clothing. Use only non-sparking tools. Good housekeeping standards and regular safe removal of waste materials will minimise the risks of spontaneous combustion and other fire hazards. Vapours are heavier than air and may spread along floors. Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. Provide adequate ventilation. The product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard. Preparation may charge electrostatically: always use earthing leads when transferring from one container to another. Keep container tightly closed. Keep away from open flames, hot surfaces and sources of ignition. Avoid contact with skin and eyes. Do not breathe vapours or spray mist. When using, do not eat, drink or smoke. Do not use pressure to empty drums. Store in original container.

### Storage:

Containers which are opened must be carefully resealed and kept upright to prevent leakage. Take notice of the directions of use on the label. Keep in a dry, cool and well-ventilated place. Keep away from heat and sources of ignition. Keep away from direct sunlight. Store in a place accessible by authorized persons only. Do not smoke.

### Storage temperature:

10 - 30 C

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### Exposure limits:

#### Australia:

Ingredient Name CAS-No.	Australia OELs - TWA	Australia OELs - STEL	Australia OELs - Skin Designation
n-BUTYL ACETATE 123-86-4	150 ppm TWA 713 mg/m <sup>3</sup> TWA	200 ppm STEL 950 mg/m <sup>3</sup> STEL	
1,2,4-TRIMETHYLBENZENE 95-63-6	123 mg/m <sup>3</sup> , 25 PPM		
ACETONE 67-64-1	1185 mg/m <sup>3</sup> TWA 500 ppm TWA	1000 ppm STEL 2375 mg/m <sup>3</sup> STEL	
2-BUTOXYETHYL ACETATE 112-07-2	133 mg/m <sup>3</sup> TWA 20 ppm TWA	333 mg/m <sup>3</sup> STEL 50 ppm STEL	Can be absorbed through the skin
XYLENE 1330-20-7	350 mg/m <sup>3</sup> TWA 80 ppm TWA	150 ppm STEL 655 mg/m <sup>3</sup> STEL	
NAPHTHALENE 91-20-3	10 ppm TWA 52 mg/m <sup>3</sup> TWA	15 ppm STEL 79 mg/m <sup>3</sup> STEL	
ETHYLBENZENE 100-41-4	100 ppm TWA 434 mg/m <sup>3</sup> TWA	125 ppm STEL 543 mg/m <sup>3</sup> STEL	
CUMENE 98-82-8	125 mg/m <sup>3</sup> TWA 25 ppm TWA	375 mg/m <sup>3</sup> STEL 75 ppm STEL	Can be absorbed through the skin

### Engineering measures:

During curing, decomposition products may be formed, which should be extracted safely from the work area. Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.

### Basic Personal Protection

#### Respiration

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

#### Hand protection:

Wear suitable gloves and eye/face protection. Use protective skin cream before handling the product.

#### Skin:

Wear as appropriate: Flame retardant antistatic protective clothing Wear shoes with conductive soles.

#### Eyes:

Wear as appropriate: Safety glasses with side-shields Goggles

### Hygiene measures:

Do not use solvents or thinners to clean skin. When using, do not eat, drink or smoke. Wash hands before breaks and at the end of workday. It is good practice in industrial hygiene to avoid contact with solvents by using appropriate protective measures whenever possible.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	liquid
Vapor pressure:	175.1879699 mmHg @68° F (20° C)
Vapor density (air = 1.0):	5.5
Solubility in water:	not determined
Flash point:	-3°C
Boiling point/range	56°C
Specific Gravity	.87
Evaporation rate (butyl acetate = 1.0):	5.6

## 10. STABILITY AND REACTIVITY

**Stability:** Stable under normal conditions.

## 10. STABILITY AND REACTIVITY

<b>Conditions to avoid:</b>	Stable under recommended storage conditions.
<b>Materials to avoid:</b>	Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.
<b>Hazardous Polymerization:</b>	None anticipated.
<b>Hazardous decomposition products:</b>	Hazardous decomposition products may be produced when the recommended processing temperatures or times are exceeded. Carbon monoxide Carbon dioxide (CO <sub>2</sub> ) Smoke nitrogen oxides (NO <sub>x</sub> )

## 11. TOXICOLOGICAL INFORMATION

### Potential Acute Health Effects:

**Eye contact:**

Causes eye irritation.

**Skin contact:**

May cause skin irritation.

**Ingestion:**

Aspiration hazard if swallowed - can enter lungs and cause damage.

**Inhalation:**

Harmful by inhalation.

May cause irritation of respiratory tract.

**Target Organ and Other Health Effects:**

Kidney injury may occur.

Causes headache, drowsiness or other effects to the central nervous system.

Liver injury may occur.

Blood disorders

Contains glycol ether which has been shown to cause blood effects damage in laboratory animals.

If this section is blank, no information is available.

## 12. ECOLOGICAL INFORMATION

**Air Pollutant**

Local pollution requirements may apply to the use of this product. Do not let product enter drains. Do not contaminate surface water.

## 13. DISPOSAL CONSIDERATIONS

**Waste disposal methods:**

Do not let product enter drains. Do not contaminate ponds, waterways or ditches with chemical or used container. Where possible recycling is preferred to disposal or incineration. Dispose of as special waste in compliance with local and national regulations.

## 14. TRANSPORTATION INFORMATION

**Australia ADG:**

<b>Proper shipping name:</b>	PAINT
<b>UN/ID No:</b>	UN1263
<b>Hazard class:</b>	3
<b>Packing group:</b>	II
<b>Hazchem Code:</b>	3[Y]E

**IMDG:**

<b>Proper shipping name:</b>	PAINT
<b>UN/ID No:</b>	UN1263

## 14. TRANSPORTATION INFORMATION

**Hazard class:** 3  
**Packing group:** II

### IATA:

**Proper shipping name:** Paint  
**UN/ID No:** UN1263  
**Hazard class:** 3  
**Packing group:** II

## 15. REGULATORY INFORMATION

### AICS Australian Inventory:

This product/preparation is in compliances with the Australian Inventory of Chemical Substances (AICS) list.

### Label Information:

#### contains

NAPHTHALENE

### Indication of danger:

F - Highly flammable Xn - Harmful N - Dangerous for the environment



### Risk Phrases

R11 - Highly flammable.  
R20 - Harmful by inhalation.  
R36 - Irritating to eyes.  
R40 - Limited evidence of a carcinogenic effect.  
R65 - Harmful: may cause lung damage if swallowed.  
R51/53 - Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

### S-phrases(s)

S 9 - Keep container in a well-ventilated place.  
S16 - Keep away from sources of ignition - No smoking.  
S33 - Take precautionary measures against static discharges.  
S60 - This material and its container must be disposed of as hazardous waste.  
S61 - Avoid release to the environment. Refer to special instructions/safety data sheets.  
S23 - Do not breathe gas/fumes/vapour/spray.  
S51 - Use only in well-ventilated areas.  
S62 - If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.  
S36/37 - Wear suitable protective clothing and gloves.

## 16. OTHER INFORMATION

**Print Date:** 11/Jan/2010  
**Revision Date:** 04/Jan/2010

## 16. OTHER INFORMATION

### Abbreviations:

NOHSC - National Occupational Health and Safety Commission, AICS - Australia Inventory of Chemical Substances, EC - European Community, ADR - Australia Code for the Transportation of Dangerous Goods by Road and Rail, IATA - International Air Transport Association, IMDG - International Maritime Dangerous Goods, NA - Not applicable, NOT ESTAB - Not established, N.A.V. - Not available, WT - Weight, mg/m<sup>3</sup> - Milligrams per cubic meter, G/L - Grams per liter, MM - Millimeters, MPPCF - Millions of particles per cubic foot, PPM - parts per million, PPT - parts per thousand, TCC/PM - Tag closed cup / Pensky-Martens, PB - Lead, PEL - Permissible exposure level, TWA - Time Weighted Average, STEL - Short term exposure limit, C - Celsius, F - Fahrenheit

### Disclaimer:

The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Valspar assumes no obligation or liability for use of this information. UNLESS VALSPAR AGREES OTHERWISE IN WRITING, VALSPAR MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. VALSPAR WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES. Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option.