



# Material Safety Data Sheet

## 1. PRODUCT AND COMPANY IDENTIFICATION

### Product Identification

**Product ID:** EKP200  
**Product Name:** EPOXY PRIMER ACTIVATOR  
**Product Use:** Paint product.  
**Print date:** 14/Sep/2009  
**Revision Date:** 21/Apr/2009

### Company Identification

De Beer Australasia Pty Ltd  
Unit 11, 8 Kerta Road,  
Kincumber NSW Australia 2258

Tel: +61 (2) 4368 4054  
Fax: +61 (2) 4368 4215

### 24-Hour Medical Emergency

**Phone:** Poisons Information Centre: Australia 131 126

## 2. HAZARDS IDENTIFICATION

### Primary Routes of Exposure:

Inhalation  
Ingestion  
Skin absorption

### Eye Contact:

- Causes eye burns.
- Risk of serious damage to eyes.

### Skin Contact:

- Causes skin burns.
- Harmful if absorbed through skin.
- May cause sensitization by skin contact.

### Ingestion:

- Causes digestive tract burns.
- Harmful if swallowed.
- Aspiration hazard if swallowed - can enter lungs and cause damage.

### Inhalation:

- Causes respiratory tract irritation.
- Harmful by inhalation.
- May cause sensitization by inhalation.
- Difficulty in breathing

**Acute Other Health Effects:**

- Contains ingredients which are corrosive.

**Target Organ and Other Health Effects:**

- Causes headache, drowsiness or other effects to the central nervous system.
- Liver injury may occur.
- Kidney injury may occur.
- Blood disorders
- Hearing loss.

**This product contains ingredients that may contribute to the following potential chronic health effects:**

- Notice: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.
- Possible sensitization.

**3. COMPOSITION / INFORMATION ON HAZARDOUS INGREDIENTS**

| Ingredient Name<br>CAS-No. | Approx.<br>Weight % | Chemical Name        |
|----------------------------|---------------------|----------------------|
| PROPRIETARY RESIN          | 25 - 30             | PROPRIETARY RESIN    |
| POLYAMINOAMIDE<br>UNKNOWN  | 25 - 30             | PROPRIETARY RESIN    |
| N-BUTYL ALCOHOL<br>71-36-3 | 20 - 25             | n-Butyl alcohol      |
| BENZYL ALCOHOL<br>100-51-6 | 20 - 25             | Benzyl alcohol       |
| PROPRIETARY ADDITIVE       | 1 - 5               | PROPRIETARY ADDITIVE |

If this section is blank there are no hazardous components per OSHA guidelines.

**4. FIRST AID MEASURES****Eye Contact:**

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lenses. If medical assistance is not immediately available, flush an additional 15 minutes. Get medical attention immediately.

**Skin Contact:**

Remove contaminated clothing and shoes. Wash off immediately with plenty of water for at least 15 minutes. Do not use soap. If skin surface is damaged, apply a clean dressing. Do not apply greases or ointments. If medical assistance is not immediately available, flush an additional 15 minutes. Get medical attention immediately.

**Ingestion:**

Give one or two glasses of water. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. If vomiting occurs, keep head lower than hips to prevent aspiration. Get medical attention immediately. Rinse mouth with water. Only induce vomiting at the instruction of medical personnel.

**Inhalation:**

Move injured person into fresh air and keep person calm under observation. Get medical attention immediately. For breathing difficulties, oxygen may be necessary. If breathing stops, provide artificial respiration.

**Medical conditions aggravated by exposure:**

Any respiratory or skin condition.

## 5. FIRE FIGHTING MEASURES

|                                  |   |
|----------------------------------|---|
| Flash point (Fahrenheit):        | 99°F (37°C)   |
| Lower explosive limit:           | 1 %   |
| Upper explosive limit:           | 11 %  |
| Autoignition temperature:        | not determined -°F (°C)   |
| Sensitivity to impact:           | no  |
| Sensitivity to static discharge: | Subject to static discharge hazards. Please see bonding and grounding information in Section 7. |
| Hazardous combustion products:   | See Section 10.   |

### Unusual fire and explosion hazards:

None known.

### Extinguishing media:

Carbon dioxide, dry chemical, foam and/or water fog.

### Fire fighting procedures:

Firefighters should be equipped with self-contained breathing apparatus and turn out gear. Keep containers and surroundings cool with water spray.

## 6. ACCIDENTAL RELEASE MEASURES

### Action to be taken if material is released or spilled:

Ventilate the area. Avoid breathing dust or vapor. Use self-containing breathing apparatus or airmask for large spills in a confined area. Wipe, scrape or soak up in an inert material and put in a container for disposal. See section 7, "Handling and Storage", for proper container and storage procedures. Remove all sources of ignition. Soak up with inert absorbent material. Use only non-sparking tools. Avoid all personal contact.

## 7. HANDLING AND STORAGE

### Precautions to be taken in handling and storage:

Keep away from heat, sparks and open flame. - No smoking. Keep container closed when not in use. Do not store above 120 degrees F. (49 degrees C). Based on flash point and vapor pressure, suitable storage should be provided in accordance with OSHA regulation 1910.106, Ontario OH&S regulation 851 section 22. Empty containers may contain product residue, including flammable or explosive vapors. Do not cut, puncture or weld on or near container. All label warnings must be observed until the container has been commercially cleaned or reconditioned. If the product is used near or above the flashpoint, an ignition hazard may be present. Activities, uses, or operations which liberate vapor (such as mixing or free fall of liquids) may also present an ignition hazard. Please ensure containers and other interconnected equipment are properly bonded and grounded at all times.

## 8. PERSONAL PROTECTIVE EQUIPMENT AND EXPOSURE CONTROLS

### Personal Protective Equipment

#### Eye and face protection:

Wear chemical goggles with splash shields or face shield. Contact lenses should not be worn when working with chemicals because contact lenses may contribute to the severity of an eye injury in case of exposure.

#### Skin protection:

Gloves: Neoprene or other nonporous.

#### Other Personal Protection Data:

To prevent skin contact wear protective clothing covering all exposed areas. Ensure that eyewash stations and safety showers are close to the workstation location. Chemical resistant apron

### Respiratory protection:

If exposure cannot be controlled below applicable limits, use the appropriate NIOSH approved respirator such as an air purifying respirator with organic vapor cartridge and dust/mist filter. Consult the respirator manufacturer's literature to ensure that the respirator will provide adequate protection. Read and follow all respirator manufacturer's instructions.

### Ventilation

Use only in well-ventilated areas. Ensure adequate ventilation, especially in confined areas. Ovens used for curing should contain a fresh air purge to prevent vapours from accumulating and creating a possible explosive mixture. Where the product is used in a hazardous classified area, use explosion-proof electrical/ventilating/lighting/equipment.

### Exposure Guidelines

#### OSHA Permissible Exposure Limits (PEL's)

| Ingredient Name<br>CAS-No. | Approx.<br>Weight % | TWA (final)                   | Ceilings limits (final) | Skin designations |
|----------------------------|---------------------|-------------------------------|-------------------------|-------------------|
| N-BUTYL ALCOHOL<br>71-36-3 | 20 - 25             | 300 mg/m <sup>3</sup> 100 ppm |                         |                   |

#### ACGIH Threshold Limit Value (TLV's)

| Ingredient Name<br>CAS-No. | Approx.<br>Weight % | TWA    | STEL | Ceiling limits | Skin designations |
|----------------------------|---------------------|--------|------|----------------|-------------------|
| N-BUTYL ALCOHOL<br>71-36-3 | 20 - 25             | 20 ppm |      |                |                   |

## 9. PHYSICAL PROPERTIES

|   |                               |
|---|-------------------------------|
| Odor:                                   | Normal for this product type. |
| Physical State:                         | liquid                        |
| pH:                                     | not determined                |
| Vapor pressure:                         | 3 mmHg @ 70°F (21.11°C)       |
| Vapor density (air = 1.0):              | 5.1                           |
| Boiling point:                          | not determined                |
| Solubility in water:                    | not determined                |
| Coefficient of water/oil distribution:  | not determined                |
| Density (lbs per US gallon):            | 8.06                          |
| Specific Gravity:                       | .97                           |
| Evaporation rate (butyl acetate = 1.0): | 0.5                           |
| Flash point (Fahrenheit):               | 99°F (37°C)                   |
| Lower explosive limit:                  | 1 %                           |
| Upper explosive limit:                  | 11 %                          |
| Autoignition temperature:               | not determined -°F (°C)       |

## 10. STABILITY AND REACTIVITY

|                                   |  |
|-----------------------------------|--|
| Stability:                        | Stable under normal conditions.  |
| Conditions to Avoid:              | Heat.  |
| Incompatibility:                  | Strong oxidizing agents Acids or alkalis.  |
| Hazardous Polymerization:         | None anticipated.  |
| Hazardous Decomposition Products: | Carbon monoxide and carbon dioxide. Ammonia compounds. Nitrogen compounds. Aldehydes |

**Sensitivity to static discharge:** Subject to static discharge hazards. Please see bonding and grounding information in Section 7.

## 11. TOXICOLOGICAL INFORMATION

| Ingredient Name<br>CAS-No. | Approx.<br>Weight % | NIOSH - Selected LD50s and LC50s  |
|----------------------------|---------------------|---|
| N-BUTYL ALCOHOL<br>71-36-3 | 20 - 25             | Inhalation LC50 Rat : 8000 ppm/4H<br>Oral LD50 Rat : 790 mg/kg<br>Oral LD50 Mouse : 2680 mg/kg<br>Dermal LD50 Rabbit : 3400 mg/kg |
| BENZYL ALCOHOL<br>100-51-6 | 20 - 25             | Oral LD50 Rat : 1230 mg/kg<br>Oral LD50 Mouse : 1360 mg/kg<br>Dermal LD50 Rabbit : 2 gm/kg  |

**Mutagens/Teratogens/Carcinogens:** None known.

## 12. ECOLOGICAL DATA

No information on ecology is available.

## 13. DISPOSAL CONSIDERATIONS

Disposal should be made in accordance with federal, state and local regulations.

## 14. TRANSPORTATION INFORMATION

### U.S. Department of Transportation

Proper Shipping Name: PAINT  
Hazard Class: 3  
UN ID Number (msds): UN1263  
Packing Group: III  
Hazardous Ingredient N-BUTYL ALCOHOL  
(Land) 1

### U.S. Highway & Rail Shipments

The supplier may apply one of the following exceptions: Combustible Liquid, Consumer Commodity, Limited Quantity, Viscous Liquid, Does Not Sustain Combustion, or others, as allowed under 49CFR Hazmat Regulations. Please consult 49CFR Subchapter C to ensure that subsequent shipments comply with these exceptions.

### Reportable Quantity Description:

### International Air Transport Association (IATA):

Proper Shipping Name: Paint  
Hazard Class: 3  
UN ID Number (msds): UN1263  
Packing Group: III  
IATA N.O.S. Technical Name 1 N-BUTYL ALCOHOL

### International Maritime Organization (IMO):

Proper Shipping Name: PAINT  
Hazard Class: 3  
IMO UN/ID Number (msds): UN1263  
Packing Group: III  
IMDG N.O.S. Technical Name 1 N-BUTYL ALCOHOL

## 15. REGULATORY INFORMATION

## 15. REGULATORY INFORMATION

### U.S. FEDERAL REGULATIONS:

| Ingredient Name<br>CAS-No. | Approx.<br>Weight % | SARA 302 | SARA 313  | CERCLA RQ in lbs. |
|----------------------------|---------------------|----------|---|-------------------|
| N-BUTYL ALCOHOL<br>71-36-3 | 20 - 25             |          | form R reporting required<br>for 1.0% de minimis<br>concentration | 5000              |

### SARA 311/312 Hazard Class:

Acute: yes  
Chronic: yes  
Flammability: yes  
Reactivity: no  
Sudden Pressure: no

### U.S. STATE REGULATIONS:

#### Right to Know:

The specific chemical identity of a component may be withheld as a trade secret under 34 Pennsylvania Code, Chapter 317.

#### Pennsylvania Right To Know:

|                      |              |
|----------------------|--------------|
| PROPRIETARY ADDITIVE | Trade Secret |
| BENZYL ALCOHOL       | 100-51-6     |
| POLYAMINOAMIDE       | UNKNOWN      |
| PROPRIETARY RESIN    | Trade Secret |
| N-BUTYL ALCOHOL      | 71-36-3      |

#### Rule 66 status of product

Not photochemically reactive.

### INTERNATIONAL REGULATIONS - Chemical Inventories

#### US TSCA Inventory:

All components of this product are in compliance with U.S. TSCA Chemical Substance Inventory Requirements.

#### Canada Domestic Substances List:

Not all components in this product are listed on the Domestic Substances List.

## 16. OTHER INFORMATION

### HMIS Codes

Health: 3\*  
Flammability: 3  
Reactivity: 1  
PPE: X - See Section 8 for Personal Protective Equipment (PPE).

### Abbreviations:

OSHA - Occupational Safety and Health Administration, IARC - International Agency for Research on Cancer, NIOSH - National Institute of Occupational Safety and Health, NTP - National Toxicology Program, ACGIH - American Conference of Governmental Industrial Hygienists, SCAQMD - South Coast Air Quality Management District, TSCA - Toxic Substances Control Act, IATA - International Air Transport Association, IMO - International Maritime Organization, DOT - Department of Transportation, NA - Not applicable, NOT ESTAB - Not established, N.A.V. - Not available, RQ - Reportable quantity, WT - Weight, MG/CU M - Milligrams per cubic meter, G/L - Grams per liter, MM - Millimeters, MPPCF - Millions of particles per cubic foot, PPM - parts per million, PPT - parts per thousand, TCC/PM - Tag closed cup / Pensky-Martens, PB - Lead, PEL - Permissible exposure level, TWA - Time Weighted Average, STEL - Short term exposure limit, C - Celsius, F - Fahrenheit.

**Disclaimer:**

The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Valspar assumes no obligation or liability for use of this information. UNLESS VALSPAR AGREES OTHERWISE IN WRITING, VALSPAR MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. VALSPAR WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES. Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option. This MSDS contains additional information required by the state of Pennsylvania.

**Preparation Information:**

|                |                               |
|----------------|-------------------------------|
| Prepared By:   | Regulatory Affairs Department |
| Print date:    | 14/Sep/2009                   |
| Revision Date: | 21/Apr/2009                   |